

*Note: This data sheet is for informational purposes. It is not a commitment to deliver hardware features or functionality. The development, release and timing of features and functionality described in this document are at the sole discretion of Five9 Network Systems.*

## FIVE9NS T3105 SERVER



### HIGHLIGHTS:

- Variety of expansion slots
- Tower form factor
- Supports Windows, Linux, and Solaris Operating Systems
- Remote system management capabilities ideal for central office and other demanding environments
- Easy to customize and integrate into existing infrastructure
- Easy to scale out as business needs to grow.



*The Five9NS T3105 is an entry-level, single socket, tower server. Powered by an Intel E3-1200V3 series or a G3000 series processor, this high-performance system provides I/O slot flexibility that enables seamless integration into a variety of OEM applications.*

### Flexible Tower Server

The Five9NS T3105 was designed with OEM needs in mind. With its rich feature set – including 4 expansion slots, remote management capabilities, and high performance Intel Xeon E3-1200v3 series processor it's an ideal fit for commercial printing and healthcare environments.

### Specialty Services

OEM customers can choose from a host of services that will accelerate the integration process and reduce time to market.

With our in-house Product Lifecycle Management service, Five9NS is uniquely positioned to architect systems for OEM customers. The Five9NS T3105 tower server is customizable and you can brand it as your own. We also provide free engineering support via experts who understand the unique requirements of OEM customers.

The Five9NS Product Lifecycle Management service aims to help you proactively manage your product lifecycle. We'll implement a product lifecycle matched to your needs, providing up to a 5-year product life from the date of contract, which can be extended upon request.

*Note: This data sheet is for informational purposes. It is not a commitment to deliver hardware features or functionality. The development, release and timing of features and functionality described in this document are at the sole discretion of Five9 Network Systems.*

## FIVE9NS T3105 SERVER

FEATURES	PRODUCT
<b>Form Factor</b>	Tower (18.8" D x 7.2" W x 15.1" H)
<b>Processors</b>	Intel Xeon E3-1200 v3 Series (4 cores) Intel Core i3-4000 Series (Specific SKUs, 2 cores) Intel Pentium G3000 Series (2 cores)
<b>Processor Sockets</b>	One (LGA1150)
<b>Chipset</b>	Intel C222, C224 or C226
<b>Memory</b>	Up to 32GB (using UDIMMs) 4 DIMM sockets, DDR3-1333 or DDR3-1600 ECC
<b>I/O Slots</b>	1 PCIe x8 slot, full height 1 PCIe x8 slot, full height 1 PCIe x4 slot, full height 1 PCIe x1 slot, full height
<b>Drive Bays</b>	One 3.5" SATA bay
<b>Hard Drives/SSDs</b>	3.5 inch SATA HDD 2.5 inch SATA HDD 2.5 inch SATA SSD
<b>Network Interface</b>	Dual Gigabit Ethernet
<b>Serial Ports</b>	2 DB9 (1 rear, 1 header)
<b>USB Ports</b>	7 ports (4 rear, 2 front, 1 internal Type A)
<b>Power Supply</b>	Single 350W AC
<b>Video</b>	Intel® HD Graphics P4700
<b>Management Hardware</b>	Integrated IPMI 2.0 BMC, RMM4 Compatible (certain SKUs only)
<b>Operating Systems</b>	Linux, Windows, Solaris